

Environmental (Indoor/Outdoor) Measurements

Clean Room Monitoring

Easily re-configurable using software

Selectable measurement in °F or °C

Time, date and unit synchronized with PC

TECHNICAL SPECIFICATIONS

	Sept and the sept at the sept	All the county and the county	100
		HYGRO-L	1
	Description	Portable Temperature & Humidity Logger	
	Inputs	2 Nos. (Inbuilt Sensor)	
	Input Types	Temperature and Humidity	ini in
	Display	Alphanumeric LCD Display	ì
	Range	Temperature: - 40°C to 60°C Humidity: 10% to 99% RH	i i
	Accuracy	Temperature: ± 1.0°C under 0°C-50°C Humidity: ± 4% under 20%-80%	
	Logging Mode	Continuous	
á	Logging Interval	60 seconds to 4 hours	
5	Data Storage	Max. 16,320 temperature and relative humidity readings	7
	PC Interface	USB mini port	
	Reports	CSV File (EXCEL FORMAT)	
	Software	Historical Data Report & Graph with Management Settings	
Ų	Software Requisites	Windows 2000/ XP/ Vista / 7 /8	
9	Power	Single 3V Lithium battery	
50.0	Operating Temperature	0°C - 60°C	
è	Size	86 x 60 x 19mm(L x W x H)	P
	Weight	90gms (With Included Package : 158gms)	

Package include:

- 1 x data logger unit
- 1 x USB cable
- 1 x 3V Lithium Battery (CR2032)

- 1 x CD ROM
- 1 x Instruction manual
- 1 x CD ROM





A/306 Bhoomi Utsav, M G Road, Besides Kala Hanuman Temple Kandivali (W), MUMBAI - 400067

Dealer Stamp